

explosion protected Double LED Navigation Lights S64 (Base) for vessels over 50 m



Type (Item-No.)	Weight (g)	Energy consumption (W)	Visibility (nm)	Diameter / Height (mm)	Voltage (V DC)
-----------------	------------	------------------------	-----------------	------------------------	----------------

Port (130.61ex)		480	1,9	3	64 / 65	24
Starboard (131.62ex)		480	2,0	3	64 / 65	24
Stern (132.60ex)		480	1,7	3	64 / 65	24
Stern Suez red (132.61ex)		480	2,1	3	64 / 65	24
Stern Kiel canal green (132.62ex)		480	1,7	3	64 / 65	24
Towing yellow (132.63ex)		480	2,1	3	64 / 65	24
Masthead 6 nm (134.60ex)		550	9,8	6	64 / 81	24
All-round, white (135.60ex)		450	2,9	3	64 / 65	24
All-round, red (135.61ex)		450	3,3	3	64 / 65	24
All-round, green (135.62ex)		450	3,1	3	64 / 65	24
All-round, yellow (135.63ex)		450	2,9	3	64 / 65	24
Signal light, white, 180° (135.60-180ex)		520	2,4	3	64 / 65	24
Signal light, red, 180° (135.61-180ex)		520	2,8	3	64 / 65	24
Signal light, green, 180° (135.62-180ex)		520	2,7	3	64 / 65	24
Signal light, yellow, 180° (135.63-180ex)		520	2,4	3	64 / 65	24

light source	High Power LED
operating temperature	-50 °C to 55 °C
storage temperature	-50 °C to 80 °C
life time	> 100.000 h
maintenance	maintenance free
connection	four-wire 1 mm ² , about 1,5 m
housing	anodized aluminum borosilicate glass stainless steel A316
protection class	IP 67 / 68
approvals	0098

II 3G Ex nA IIC T4 GC
II 3D Ex tc IIC T130 °C DC