

LED Navigation Lights S64 (Base) for vessels up to 50 m



Type (Item-No.)		Weight (g)	Energy consumption (W)	Visibility (nm)	Diameter / Height (mm)	Voltage (V DC)
Port (130.01)		480	0,8	2	64 / 65	12 / 24
Starboard (131.02)		480	0,7	2	64 / 65	12 / 24
Stern (132.00)		480	0,7	2	64 / 65	12 / 24
Stern Suez red (132.01)		480	2,1	3	64 / 65	12 / 24
Stern Kiel canal green (132.02)		480	1,7	3	64 / 65	12 / 24
Towing yellow (132.03)		480	0,7	2	64 / 65	12 / 24
Masthead 3 nm (133.00)*		460	1,8	3	64 / 65	12 / 24
Masthead 5 nm (134.00)		460	5	5	64 / 65	24
All-round, white (135.00)		450	1	2	64 / 65	12 / 24
All-round, red (135.01)		450	1,1	2	64 / 65	12 / 24
All-round, green (135.02)		450	1	2	64 / 65	12 / 24
All-round, yellow (135.03)		450	1	2	64 / 65	12 / 24
Signal light, white, 180° (135.00-180)		520	0,9	2	64 / 65	12 / 24
Signal light, red, 180° (135.01-180)		520	1	2	64 / 65	12 / 24
Signal light, green, 180° (135.02-180)		520	0,9	2	64 / 65	12 / 24
Signal light, yellow, 180° (135.03-180)		520	0,9	2	64 / 65	12 / 24
Bicolor (136.08)*		480	1,2	2	64 / 65	12 / 24
Tricolor (137.08)*		480	1,6	2	64 / 65	12 / 24
Tricolor / Anchor (138.08) *		480	1,6/1,2	2	64 / 65	12 / 24

*for vessel ut to 20 m

light source	High Power LED
operating temperature	-50 °C to 55 °C
storage temperature	-50 °C to 80 °C
life time	> 120.000 h
maintenance	maintenance free
connection	two-wire 1 mm ² , about 1,5 m
housing	anodized aluminum borosilicate glass stainless steel A316
protection class	IP 67 / 68
approvals	0098