

LED Navigation Lights S64 (Classic) for vessels up to 50 m



Type (Item-No.)		Weight (g)	Energy consumption (W)	Visibility (nm)	Diameter / Height (mm)	Voltage (V DC)
Port (150.01)		540	0,8	2	64 / 54	12 / 24
Starboard (151.02)		540	0,7	2	64 / 54	12 / 24
Stern (152.00)		540	0,7	2	64 / 54	12 / 24
Stern Suez red (152.01)		540	2,1	3	64 / 65	12 / 24
Stern Kiel canal green (152.02)		540	1,7	3	64 / 65	12 / 24
Towing yellow (152.03)		540	0,7	2	64 / 54	12 / 24
Masthead 3 nm (153.00)*		520	1,8	3	64 / 54	12 / 24
Masthead 5 nm (154.00)		520	5	5	64 / 54	24
All-round, white (155.00)		510	1	2	64 / 54	12 / 24
All-round, red (155.01)		510	1,1	2	64 / 54	12 / 24
All-round, green (155.02)		510	1	2	64 / 54	12 / 24
All-round, yellow (155.03)		510	1	2	64 / 54	12 / 24
Signal light, white, 180° (155.00-180)		580	0,9	2	64 / 54	12 / 24
Signal light, red, 180° (155.01-180)		580	1	2	64 / 54	12 / 24
Signal light, green, 180° (155.02-180)		580	0,9	2	64 / 54	12 / 24
Signal light, yellow, 180° (155.03-180)		580	0,9	2	64 / 54	12 / 24
Bicolor (156.08)*		540	1,2	2	64 / 54	12 / 24
Tricolor (157.08)*		540	1,6	2	64 / 54	12 / 24
Tricolor / Anchor (158.08) *		540	1,6/1,2	2	64 / 54	12 / 24

*for vessel ut to 20 m

light source	High Power LED
operating temperature	-50 °C to 55 °C
storage temperature	-50 °C to 80 °C
life time	> 120.000 h
maintenance	maintenance free
connection	two-wire 1 mm ² , about 1,5 m
housing	Bronze CW307G borosilicate glass stainless steel A316
protection class	IP 67 / 68
approvals	0098